

Serie PEZ



MODELO	PEZ-35JA		PEZ-50JA		PEZ-60JA		PEZ-71JA		PEZ-100JA		PEZ-125JA		PEZ-140JA		
UNIDAD INTERIOR	PEAD-RP35JA		PEAD-RP50JA		PEAD-RP60JA		PEAD-RP71JA		PEAD-RP100JA		PEAD-RP125JA		PEAD-RP140JA		
UNIDAD EXTERIOR	PUHZ-RP35VHA		PUHZ-RP50VHA		PUHZ-RP60VHA		PUHZ-RP71VHA		PUHZ-RP100V ó YKA		PUHZ-RP125V ó YKA		PUHZ-RP140V ó YKA		
Función	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	
Capacidad	kW		5,0(2,3-5,6)		6,0(2,5-7,3)		7,1(3,3-8,1)		8,0(3,5-10,2)		10,0(4,9-11,4)		11,2(4,5-14)		
	kCal/h		4300		5160		6106		6880		8600		9632		
Consumo Total	W		1,55		1,60		2,03		2,00		2,77		2,72		
Función	V-F-50Hz	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR
Tensión	230-I		230-I		230-I		230-I		230-I		400-III		400-III		
Coefficiente Eficacia Energética	3,53		3,23		3,75		3,50		4,00		3,61		4,12		
Etiquetado Energético	A		A		A		A		A		A		A		
	A		A		A		A		A		A		A		
Unidad Interior	Caudal de aire ⁽¹⁾	m3/min		10 / 12 / 14		12 / 14,5 / 17		14,5 / 18 / 21		17,5 / 21 / 25		24 / 29 / 34		29,5 / 35,5 / 42	
	Presión estática	Pa		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150	
	Nivel sonoro ⁽³⁾	dB (A)		23 / 27 / 30		26 / 31 / 35		25 / 29 / 33		26 / 30 / 34		29 / 34 / 38		33 / 36 / 40	
	Dimensiones ⁽²⁾	mm		900 / 732 / 250		900 / 732 / 250		1.100 / 732 / 250		1.100 / 732 / 250		1.400 / 732 / 250		1.400 / 732 / 250	
	Peso	Kg		26		28		33		33		41		43	
Unidad Exterior	Caudal de aire	m3/min		35		35		60		60		110		120	
	Nivel sonoro ⁽⁴⁾	dB (A)		44 (41) / 46		44 (41) / 46		47 (44) / 48		47 (44) / 48		49 (46) / 51		50 (47) / 52	
	Dimensiones ⁽²⁾	mm		800 / 300 + 23 / 600		800 / 300 + 23 / 600		950 / 330 + 30 / 943		950 / 330 + 30 / 943		1050 / 330 + 30 / 1338		1050 / 330 + 30 / 1338	
	Peso	Kg		42		42		67		67		116 / 124		116 / 126	
	Conexión Frigorífica	Líquido	mm		6,35 (1/4")		6,35 (1/4")		9,52 (3/8")		9,52 (3/8")		9,52 (3/8")		9,52 (3/8")
	Gas	mm		12,7 (1/2")		12,7 (1/2")		15,88 (5/8")		15,88 (5/8")		15,88 (5/8")		15,88 (5/8")	
Distancias Frigoríficas (Máx. Vert./Total)	m		30 / 50		30 / 50		30 / 50		30 / 50		30 / 75		30 / 75		

Notas: (1). Baja/Media/Alta velocidad(2). Dimensiones: Ancho/Fondo/Alt(3). Bajo/Medio/Alto(4). (Silent Operation Mode)



PEAD-RP35~140JA



PUHZ-RP35/50VHA



PUHZ-RP60/71VHA



PUHZ-RP100/125/140V
ó YKA



CONTROL REMOTO
ó YKA