

**Serie SPEZ**

**Standard Inverter**

MODELO		SPEZ-35JA		SPEZ-50JA		SPEZ-60JA		SPEZ-71JA		SPEZ-100JA		SPEZ-125JA		SPEZ-140JA													
UNIDAD INTERIOR		PEAD-RP35JA		PEAD-RP50JA		PEAD-RP60JA		PEAD-RP71JA		PEAD-RP100JA		PEAD-RP125JA		PEAD-RP140JA													
UNIDAD EXTERIOR		SUZ-KA35VA		SUZ-KA50VA		SUZ-KA60VA		SUZ-KA71VA		PUHZ-P100V ó YHA		PUHZ-P125V ó YHA		PUHZ-P140V ó YHA													
Función		FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR												
Capacidad	kW	3,6 (1,0-3,9)	4,1 (0,9-5)	4,9 (1,1-5,6)	5,9 (0,9-7,2)	5,7 (1,1-6,3)	7,0 (0,9-8)	7,1 (0,9-8,1)	8,0 (0,9-10,2)	9,4 (4,9-11,2)	11,2 (4,5-12,5)	12,3 (5,5-14)	14,0 (5-16)	13,6 (5,5-15)	16,0 (5-18)												
	kCal/h	3.096	3.526	4.214	5.074	4.902	6.020	6.106	6.880	8.084	9.632	10.578	12.040	11.696	13.760												
Consumo Total		W		1,06	1,11	1,52	1,62	1,68	1,94	2,21	2,09	3,04	3,10	4,22	3,87	4,52	4,43										
Función		FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR	FRÍO	CALOR										
Tensión		V-F-50Hz		230-I		230-I		230-I		230-I		230-I		400-III		230-I		400-III									
Coeficiente Eficacia Energética		3,40		3,69		3,22		3,64		3,39		3,61		3,21		3,83		3,09		3,61							
Etiquetado Energético		A		A		A		A		A		A		B		A		C		A							
Unidad Interior	Caudal de aire <sup>(1)</sup>	m3/min		10 / 12 / 14		12 / 14,5 / 17		14,5 / 18 / 21		17,5 / 21 / 25		24 / 29 / 34		29,5 / 35,5 / 42		32 / 39 / 46											
	Presión estática	Pa		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150		35 / 50 / 70 / 100 / 150											
	Nivel sonoro <sup>(3)</sup>	dB (A)		23 / 27 / 30		26 / 31 / 35		25 / 29 / 33		26 / 30 / 34		29 / 34 / 38		33 / 36 / 40		34 / 38 / 43											
	Dimensiones <sup>(2)</sup>	mm		900 / 732 / 250		900 / 732 / 250		1.100 / 732 / 250		1.100 / 732 / 250		1.400 / 732 / 250		1.400 / 732 / 250		1.600 / 732 / 250											
	Peso	Kg		26		28		33		33		41		43		47											
Unidad Exterior	Caudal de aire	m3/min		33,4		49		49		49		60		100		100											
	Nivel sonoro <sup>(4)</sup>	dB (A)		47		48		53		55		53		55		50 (47)		54		51 (48)		55		52 (49)		56	
	Dimensiones <sup>(2)</sup>	mm		800 / 285 / 550		840 / 330 / 850		840 / 330 / 850		840 / 330 / 850		950 / 330 + 30 / 943		950 / 330 + 30 / 1350		950 / 330 + 30 / 1350											
	Peso	Kg		37		53		53		58		75		77		99		101		99		101					
	Conexión Frigorífica	Líquido	mm		6,35 (1/4")		6,35 (1/4")		6,35 (1/4")		9,52 (3/8")		9,52 (3/8")		9,52 (3/8")		9,52 (3/8")										
	Gas	mm		9,52 (3/8")		12,7 (1/2")		15,88 (5/8")		15,88 (5/8")		15,88 (5/8")		15,88 (5/8")		15,88 (5/8")											
Distancias Frigoríficas (Máx. Vert./Total)		m		12 / 20		30 / 30		30 / 30		30 / 30		30 / 50		30 / 50		30 / 50											

Notas: (1). Baja/Media/Alta velocidad(2). Dimensiones: Ancho/Fondo/Alt(3). Bajo/Medio/Alto(4). (Silent Operation Mode)



PEAD-RP35-140JA



PUHZ-P100V ó YHA



PUHZ-P125/140V ó YHA



SUZ-KA35VA



SUZ-KA50/60/71VA



CONTROL REMOTO